

Konsole, Art.-Nr. 30.15–30.18

Mounting brackets, item no. 30.15–30.18

Produktspezifikationen

Konsole, aus Stahl verzinkt oder Edelstahl gebürstet, Kastenprofil 40 x 30 mm, mit Verschlusskappe aus Kunststoff, auf verschweißter Grundplatte (5 mm stark)

4 Lochbohrungen (Ø 13 mm)

Art.-Nr. 30.15: L = 300 mm

Art.-Nr. 30.16: L = 400 mm

Art.-Nr. 30.17: L = 500 mm

Art.-Nr. 30.18: L = 600 mm

Hinweis: Die Tragfähigkeit der Konsolen ist abhängig von der jeweiligen Wandkonstruktion. Die Befestigungselemente sind den örtlichen Gegebenheiten entsprechend zu wählen. Die Konsole hält bei einer Verankerung in C20/25 einer Auflast von ca. 250 kg stand. Der Abstand der Konsolen untereinander ist abhängig von Material und Form der Trägerplatte (Empfehlung ≤ 625 mm).

Product Specifications

mounting bracket, galvanized steel or brushed stainless steel, box section 40 x 30 mm, with plastic end cap, on welded base plate (5 mm thick)

4 mounting holes (Ø 13 mm)

item no. 30.15: L = 300 mm

item no. 30.16: L = 400 mm

item no. 30.17: L = 500 mm

item no. 30.18: L = 600 mm

Note: Load capacity of mounting bracket depends on wall construction. Choose mounting elements according to local conditions. Maximum load of mounting bracket is approx. 250 kg given that it is fixed on concrete wall with C20/25 strength. Choose spacing between brackets according to material and design of work top (recommendation ≤ 625 mm)

Technische Bemaßung

Technical Dimensioning

